



NAVIMARE-PX
— MARINE & INDUSTRIAL COATINGS —

SYNTHETIC THINNER T-5

Catalog No 005-S-0000

FEATURES

Based on white sprit.

RECOMMENDED USES

It is used in most Alkyd paints, for thinning and cleaning

Sent. Primer, Rapid, Synthetic Finish, etc.

SPECIFICATION DATA

Color	: Clear
Density (At 20°C)	: 0.854 gr/cm ³
Odor	Petroleum smell
Packaging	: 18 Lt. Metal container .
Flash Point	: 26.6 °C
Evaporation rate	Fast

APPLICATION GUIDE

Surface Preparation

Mixing and Thinning

Application

Precautions

Refer to material safety data sheet of the product. Additional safety information is available upon request. Minimum safety precautions in dealing with the paints are;

- Take precaution to avoid skin and eye contact (i.e.gloves , goggles, face mask, barrier creams, etc.)
- Provide adequate ventilation
- If the product comes in contact with the skin, wash thoroughly with lukewarm water and soap or suitable industrial cleaner. If the eyes are contaminated flush with water (minimum 10 minutes) and obtain medical attention at once.
- Since these products contain flammable materials, keep away from sparks and open flames. No smoking should be permitted in the area.

Observe all precautionary notices on containers.

Disclaimer

This is not a specification and all information is given in good faith. Since conditions of use are beyond the manufacturer's control, information contained herein is without warranty, implied or otherwise, and final determination of the suitability of any information or material for the use contemplated, the manner of use and whether there is any infringement of patents is the sole responsibility of the user. Manufacturer does not assume any liability in connection with the use of the product relative to coverage, performance or injury. For application in special conditions, consult Navimare-PX office. for detailed recommendations